

## DESCRIPTION

Type	Track Spotlight
Article-number	141564L10102
Colour	black
Energy Consumption	44.0 W
Efficiency	68 lm/W
Luminous Flux	2998 lm
Current (sec)	1050 mA
Protection Class	IP 20
Energy-Label	G
Cooling	Passive

## LED

Color Temperature	2500K
Color Rendering	CRI 90
LES	15
Color Tolerance	3-Step McAdam
Planckian Curve	BBL
Spectrum	Bread G7
Photobiological safety	RG1

## ELECTRICAL


Overload- / Shortcircuit Protection	
Wiring / Adapter	3-Phase Adapter
Max Luminaires MCB	B16A 27Stück
Tracks	Global Stucchi Eutrac

## Control

Control	On/Off
---------	--------

## REFLECTOR

Technology	ULTRA
Material	Miro 8 Silver
FWHM	16°
FWTM	32°



I-max : 21965 cd \*

UGR : 18.2 (4H/8H - 70/50/20)

H/m	D/m	E <sub>max</sub> /lx/klm *
1.0	0.3	7327
2.0	0.6	1832
3.0	0.9	814
4.0	1.2	458

### Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2022\_10\_19